

# Examples of *multiaudience* package use

Boris Veytsman

Date: 2015/07/11 22:49:40

## Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>The <code>\CurrentAudience</code> command</b>	<b>3</b>
<b>3</b>	<b>The <code>\showto</code> command</b>	<b>3</b>
<b>4</b>	<b>The <code>showto</code> environment</b>	<b>3</b>
<b>5</b>	<b>Use of verbatim text</b>	<b>4</b>
<b>6</b>	<b>Syntactic sugar</b>	<b>4</b>
6.1	Not for admins . . . . .	5

## 1 Introduction

We defined three audiences:

```
\SetNewAudience{admins}
\SetNewAudience{devs}
\SetNewAudience{execs}
```

## 2 The `\CurrentAudience` command

The current audience is `\CurrentAudience`.

The current audience is devs.

## 3 The `\showto` command

Note the nesting here:

```
\showto{admins}{This text is visible to admins only\footnote{And
admins see a footnote}.}
\showto{admins, devs}{This text is visible to admins and
devs. \showto{devs}{This text is visible to devs.}}
\showto{-, admins}{This text is \emph{not} visible to admins.}
This text is visible to everybody\footnote{And everybody sees a
footnote}.
```

This text is visible to admins and devs. This text is visible to devs. This text is *not* visible to admins. This text is visible to everybody<sup>1</sup>.

## 4 The `shownto` environment

```
\begin{shownto}{admins}
This is for admins only.
\end{shownto}

\begin{shownto}{-, admins}
This is for everybody \emph{but} admins.
\end{shownto}
```

This is for everybody *but* admins.

---

<sup>1</sup>And everybody sees a footnote

## 5 Use of verbatim text

```
\begin{shownto}{-,execs}
We cannot use \texttt{verbatim} inside shownto, but we can use
\texttt{input} with \texttt{verbatim} inside.
```

```
We also can use \texttt{path} and \texttt{url} from hyperref package:
\path{a$2}, \url{http://borisv.lk.net/cv/cv.html\#Publications}.
\input{verbatim}
```

```
We also can use \texttt{path} and \texttt{url} from hyperref package:
\path{a$2}, \url{http://borisv.lk.net/cv/cv.html\#Publications}.
\end{shownto}
```

We cannot use `verbatim` inside `shownto`, but we can use `input` with `verbatim` inside.

We also can use `path` and `url` from `hyperref` package: `a$2`, <http://borisv.lk.net/cv/cv.html#Publications>.

This is a piece of verbatim text.  
Special symbols: `~!@#%~&*<>{}`"

Another option is the use of `\SaveVerb` and friends from `fancyvrb` package:

```
\begin{SaveVerbatim}{SavedVerb}
This is a verbatim line: ~!@#%~&*{:"'<>?
\end{SaveVerbatim}
```

```
\begin{shownto}{-,devs}
  \UseVerbatim{SavedVerb}
\end{shownto}
```

## 6 Syntactic sugar

We have a special footnote command `\Footnote{admins}`{This footnote is for admins only.}.

We have a special footnote command.

```
\begin{Subsection}{admins}[Admins-only subsection]{This subsection is
  visible only to admins}
```

We have special sectioning commands.  
`\end{Subsection}`

```
\begin{Subsection}{-,admins}[Not for admins]{This subsection is not
  visible to admins}
```

Another example. `\showto{devs}`{This is visible to devs only.}  
`\end{Subsection}`

## **6.1 This subsection is not visible to admins**

Another example. This is visible to devs only.