

The stampinclude package

Heiko Oberdiek*

2016/05/16 v1.1

Abstract

The package replaces `\includeonly` and selects the files for `\include` by inspecting the time stamp of the `.aux` file. The file is selected for inclusion if the `.aux` file does not yet exist or is older than the corresponding `.tex` file.

Contents

1	Documentation	1
1.1	Introduction	1
1.2	Usage	2
1.3	Limitations	2
1.3.1	Other file dependencies	2
1.3.2	<code>\include</code> dependencies	3
1.3.3	Summary	3
1.4	Requirements	3
2	Implementation	3
3	Installation	5
3.1	Download	5
3.2	Bundle installation	5
3.3	Package installation	5
3.4	Refresh file name databases	6
3.5	Some details for the interested	6
4	References	6
5	History	6
	[2008/07/14 v1.0]	6
	[2016/05/16 v1.1]	6
6	Index	7

1 Documentation

1.1 Introduction

L^AT_EX provides two commands `\include` and `\includeonly` that helps in organizing large projects. Example for a master file:

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

```

\documentclass{book}
% \includeonly{}
\begin{document}
\include{fileA}
\include{fileB}
\include{fileC}
\end{document}

```

All files are read and compiled if `\includeonly` is not executed. Otherwise you can give `\includeonly` a list of files in the preamble, e.g.:

```
\includeonly{fileA,fileC}
```

Now only files `fileA.tex` and `fileC.tex` are read and compiled.

If you change file `fileB.tex` and want to see only this file, then you must change the line with `\includeonly` to

```
\includeonly{fileB}
```

It is tedious to do this again and again, if different files are changed.

Package `askinclude` [1] offers a solution for this problem. It interactively asks for the files to be included and saves the user from editing the master file.

This package `stampinclude` goes another way. \LaTeX reads and writes a separate `.aux` file for each file that is included by `\include`. There \LaTeX remembers counter values. Changed `.tex` files can therefore be detected by comparing the file date stamp of the `.tex` file with the date stamp of its `.aux` file. Since version 1.30.0 `pdfTeX` provides `\pdffilemdate` that reads the file date stamp. Thus this package uses this command and redefines `\include` to include the files that do not have `.aux` files yet or that are newer than its `.aux` file. `\includeonly` is ignored.

1.2 Usage

The package is loaded as normal \LaTeX package without options:

```
\usepackage{stampinclude}
```

Alternatively the package may be loaded on the command line (Example for shell ‘bash’):

```
latex '\AtBeginDocument{\usepackage{stampinclude}}\input{master}'
```

Without `\AtBeginDocument` (and `\RequirePackage` instead of `\usepackage`) \TeX would name the document `stampinclude.dvi` instead of `master.dvi`.

1.3 Limitations

1.3.1 Other file dependencies

A file that is included by `\include` may input ore reference other files:

- other \TeX files using `\input`,
- graphics files (`\includegraphics`),
- listings of external files,
- ...

Updates of those files are not detected by this package. It limits the date stamp comparison of an `.aux` file to its `.tex` file.

1.3.2 `\include` dependencies

In the example, given in the introduction 1.1, three files `fileA`, `fileB`, and `fileC` are included in this order. Now file `fileA` is changed by adding four pages, `fileB` remains untouched, and `fileC` is also updated. Then the package only selects `fileA` and `fileC` for inclusion. File `fileB` is not included. But \LaTeX has stored the counter values that are active at the end of `fileB` in `fileB.aux` in one of the previous runs when `fileB` was included. However the later addition of four pages in `fileA` was not known at that time. Therefore `fileB.aux` is out of date and the inclusion of file `fileC` starts with wrong counter values (especially the page counter).

1.3.3 Summary

This package `stampinclude` and the `\include` feature helps in accelerating the \LaTeX compilation. But it is not intended for generating the final version. For the final version of the document it is better to include *all* files to get all counter values right. Then this package and any `\includeonly` lines should be commented out:

```
% \usepackage{stampinclude}
% \includeonly{...}
```

1.4 Requirements

- pdf \TeX v1.30.0 (because of `\pdffilemoddate` and `\pdfstrcmp`), both modes for DVI and PDF are supported.
- Alternatively Lua \TeX may be used. It lacks `\pdffilemoddate` and `\pdfstrcmp`. But its services are provided by package `pdftexcmds` [2] that is automatically loaded.

2 Implementation

```
1 \langle *package\rangle
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{stampinclude}
4 [2016/05/16 v1.1 Include files based on time stamps (H0)]%
5 \RequirePackage{pdftexcmds}[2007/12/12]%
6 \begingroup
7 \chardef\x=1 %
8 \expandafter\ifx\csname pdf@filemoddate\endcsname\relax
9 \chardef\x=0 %
10 \fi
11 \expandafter\ifx\csname pdf@strcmp\endcsname\relax
12 \chardef\x=0 %
13 \fi
14 \expandafter\endgroup\ifcase\x
15 \PackageWarningNoLine{stampinclude}{%
16 \string\pdffilemoddate\space or %
17 \string\pdfstrcmp\space are not found,\MessageBreak
18 that are provided by pdfTeX >= 1.30.0.\MessageBreak
19 Also LuaTeX is not detected.\MessageBreak
20 Therefore package loading is aborted%
21 }%
22 \expandafter\endinput
23 \fi
```

\Sinc@org@include

```
24 \let\Sinc@org@include\@include
```

\@include

```
25 \def\@include#1 {%
26   \IfFileExists{#1.aux}{%
27     \ifnum\pdf@strcmp{\pdf@filemoddate{#1.aux}}%
28       {\pdf@filemoddate{#1.tex}}<0 %
29     \ifx\@partlist\@empty
30       \gdef\@partlist{#1}%
31     \else
32       \g@addto@macro\@partlist{,#1}%
33     \fi
34   \fi
35 }{%
36   \ifx\@partlist\@empty
37     \gdef\@partlist{#1}%
38   \else
39     \g@addto@macro\@partlist{,#1}%
40   \fi
41 }%
42 \Sinc@org@include{#1} \relax
43 }
```

\includeonly Macro \includeonly is ignored.

```
44 \renewcommand*\includeonly[1]{%
45   \PackageInfo{stampinclude}{%
46     Ignoring \string\includeonly
47   }%
48 }
```

Simulate \includeonly.

```
49 \@partswtrue
50 \gdef\@partlist{}

Print included files at end of document.

51 \AtEndDocument{%
52   \begingroup
53     \expandafter\let\expandafter\@partlist\expandafter\@empty
54     \expandafter\@for\expandafter\reserved@a
55     \expandafter:\expandafter=\@partlist\do{%
56       \ifx\@partlist\@empty
57         \edef\@partlist{\reserved@a}%
58       \else
59         \edef\@partlist{\@partlist, \reserved@a}%
60       \fi
61     }%
62     \typeout{*****%
63             *****%
64             *****%
65             *****%
66     }%
67     \ifx\@partlist\@empty
68       \typeout{[stampinclude] No included files.}%
69     \else
70       \typeout{[stampinclude] Included files:}%
71       \typeout{\@partlist}%
72     \fi
```

```

73 \typeout{*****%
74          *****%
75          *****%
76          *****%
77 }%
78 \endgroup
79 }
80 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/stampinclud.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/stampinclud.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex stampinclud.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
stampinclud.sty → tex/latex/oberdiek/stampinclud.sty
stampinclud.pdf → doc/latex/oberdiek/stampinclud.pdf
stampinclud.dtx → source/latex/oberdiek/stampinclud.dtx
```

If you have a `docstrip.cfg` that configures and enables docstrip’s TDS installing feature, then some files can already be in the right place, see the documentation of docstrip.

¹[CTAN:pkg/stampinclud](#)

3.4 Refresh file name databases

If your T_EX distribution (T_EX Live, MiK_TE_X, ...) relies on file name databases, you must refresh these. For example, T_EX Live users run `texhash` or `mktextlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the `autodetect` routine about your intention:

```
latex \let\install=y\input{stampinclude.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex stampinclude.dtx
makeindex -s gind.ist stampinclude.idx
pdflatex stampinclude.dtx
makeindex -s gind.ist stampinclude.idx
pdflatex stampinclude.dtx
```

4 References

- [1] Pablo A. Straub, Heiko Oberdiek: *The askinclude package*; 2007/10/23 v2.0; [CTAN:pkg/askinclude](#).
- [2] Heiko Oberdiek: *The pdftexcmds package*; 2007/12/12 v0.3; [CTAN:pkg/pdftexcmds](#).

5 History

[2008/07/14 v1.0]

- First version.

[2016/05/16 v1.1]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\@empty</code>	29, 36, 53, 56, 67
<code>\@for</code>	54
<code>\@include</code>	24, <u>25</u>
<code>\@partlist</code>	29, 30, 32, 36, 37, 39, 50, 53, 55, 56, 57, 59, 67, 71
<code>\@partswtrue</code>	49
A	
<code>\AtEndDocument</code>	51
C	
<code>\chardef</code>	7, 9, 12
<code>\csname</code>	8, 11
D	
<code>\do</code>	55
E	
<code>\endcsname</code>	8, 11
<code>\endinput</code>	22
G	
<code>\g@addto@macro</code>	32, 39
<code>\gdef</code>	30, 37, 50
I	
<code>\ifcase</code>	14
<code>\IfFileExists</code>	26
<code>\ifnum</code>	27
<code>\ifx</code>	8, 11, 29, 36, 56, 67
M	
<code>\MessageBreak</code>	17, 18, 19
N	
<code>\NeedsTeXFormat</code>	2
P	
<code>\PackageInfo</code>	45
<code>\PackageWarningNoLine</code>	15
<code>\pdf@filemoddate</code>	27, 28
<code>\pdf@stricmp</code>	27
<code>\pdf@filemoddate</code>	16
<code>\pdfstricmp</code>	17
<code>\ProvidesPackage</code>	3
R	
<code>\renewcommand</code>	44
<code>\RequirePackage</code>	5
<code>\reserved@a</code>	54, 57, 59
S	
<code>\Sinc@org@include</code>	24, 42
<code>\space</code>	16, 17
T	
<code>\typeout</code>	62, 68, 70, 71, 73
X	
<code>\x</code>	7, 9, 12, 14